Antennas 1600 Decker Ave. San Martin, Ca. 95046 (408) 683-4240

KIM ELECTRONICS

Amplifiers 2140 Jeanie Lane Gilroy, Ca. 95020 (408) 842-7349


ASSEMBLY INSTRUCTIONS

VHF band pass Antenna

- Assemble the boom using 1½x8-32 screws, nuts and lockwashers.
 (1½x8-32 for 1½ inch dia. booms.)
- 2. Mount the four feed element insulators with 1\(\frac{1}{2}x8-32\) screws, nuts and lockwashers. (2\(\frac{1}{2}x8-32\) for 1\(\frac{1}{2}\) inch dia. booms.).
- 3. Place insulating sleeves on three straps and mount the straps and driven elements as shown in the assembly drawing. Use 1½x8-32 screws for two meter antennas and 1x6-32 screws for 220 antennas. Tighten all nuts securely. Then add a flat washer and a nut to both halves of the front driven element.
- 4. If shown on the dimension drawing, mount the loop as shown in the assembly sketch.
- 5. Mount the directors and reflector with 2x8-32 screws, nuts and lock washers. (2½x8-32 for 1½ inch dia. booms).
- 6. If you ordered a KLM balun with the antenna, mount the balun clip on top of the first director using the director mounting screw. Snap the balun into place with the <u>drain hole</u> near the connector <u>down</u>. Attach the balun leads to the feed points keeping the leads as short as possible. Route the coax along the boom and down the mast.
- 7. Attach the antenna nounting U-bolt assembly through the holes provided for either horizontal or vertical mounting. For antennas with 1½ inch booms, attach the boom to mast bracket over the center splice or at the antenna balance point. For best performance when mounting the antenna vertically, use a mast section of hard wood or other nonconducting material for four feet either side of the antenna mounting point. KLM will provide phasing instructions for installations using more than one antenna upon request.

Downloaded by RadioManual.EU

KLM 144-148-12 5052 ANTENNA



XX 5052 BALANCED FEED POINT

0.

