



VHF AND UHF TRANSCEIVERS

IC-F33GT

(VHF transceiver with 10-keypad)

IC-F43GT

(UHF transceiver with 10-keypad)

IC-F33GS

(VHF transceiver without 10-keypad)

IC-F43GS

(UHF transceiver without 10-keypad)

A new direction in Land Mobile radios

- Large channel capacity
- Wide range frequency coverage
- Lithium-ion battery standard
- Multiple tone signaling capabilities
- Built-in audio compander
- Optional SmarTrunk 3G™, voice scrambler, man down and DTMF decoder units



**BIIS 1200
Compatible**



Icom Inc.

A new direction in Land Mobile radios



The IC-F33G series is suitable for a variety of needs — large or small, mobile or stationary. Whether you are a large-scale construction site, warehouse, hospital or hotel, or a small on the go messenger service, this radio provides the built-in flexibility to handle your communication needs.

Offering advanced features such as wide frequency range, multiple signaling and loud audio, the IC-F33G series is a rugged and reliable 2-way communications tool. This is the new direction in LMR communications.

Lithium-Ion battery pack

Supplied 1150mAh Li-Ion battery pack, BP-231, provides 8/9 hours* of operating time. For longer operating time, use the BP-232 which is rated for a full 15/16 hours*. Li-Ion technology has virtually no memory charging issues. A rugged dual-rail guide securely locks the battery to the radio.

* UHF/VHF, Typical operation Tx:Rx: Stand-by=5:5:90, power save on

Wide frequency range and large channel capacity

The IC-F33G series covers a wide frequency range in one version (VHF 136–174 MHz, UHF 400–470MHz or 450–512 (520) MHz). The 256 memory channel capacity with 16 memory banks allows you to divide and store a variety of flexible channel groupings. Easy memory channel selection with a simple rotation of the rotary channel knob.

Small and lightweight body

The IC-F33G series sheds size and weight compared with previous models, weighing just 285g* (including BP-231) and measuring only 53(W)×120(H)×32.5(D) mm**. The aluminum die-cast chassis and polycarbonate casing combination meets MIL standard specifications.

* 10.0 oz, VHF version ** 2³/₃₂(W)× 4²³/₃₂(H)×1⁹/₃₂(D) in

VHF TRANSCEIVERS

IC-F33GT

With 10-keypad

IC-F33GS

Without 10-keypad

UHF TRANSCEIVERS

IC-F43GT

With 10-keypad

IC-F43GS

Without 10-keypad

Built-in multi-format tone signaling

Use the built-in CTCSS, DTCS, 2-Tone, 5-Tone or BIIS capability to set up your own talk groups and quiet stand-by when others are talking. You can also set up selective calls to individuals or control a repeater.



Multiple 2-Tone, Multiple 5-Tone

Encode or decode up to 10 2-Tone, 8 5-Tone codes on a single memory channel. This is perfect for professionals who require multiple district paging on one channel. When a matched tone is received, the following items are programmable for each code.

- Bell icon
- Answer back
- Stun
- Beep sound
- Auto transmit
- Scan

8 programmable buttons

The [P0]–[P3], [▲], [▼], [Red] and [Monitor] buttons are programmable to meet specific needs. The [Red] button on the top panel can be assigned as an emergency trigger.

Alphanumeric display

The 8-character alphanumeric display shows channel, bank, tone code and scanning channel names on the display. A separate row of operational icons indicate battery, signal strength, RX/TX and other radio conditions.

Audio compander

The built-in audio compander reduces noise components and provides clear reception even in narrow band use.

Built-in voice scrambler

The IC-F33G series includes a built-in inversion type voice scrambler in all models. When a more secure system is required, the optional voice scrambler unit UT-109 or UT-110 is available.

BIIS 1200 compatible

The following selective calling and data features are available with the built-in BIIS system.

- 32 abbreviated call memories
- 7 group IDs
- 24-status Messages
- Send 8-character SDM (Short Data Message)
- Receive up to 95 characters of free text

Other features

- 8 DTMF autodial memories
- 2 step reduced power setting
- Power saver
- Power on password
- Busy, repeater lockout functions
- Optional SmarTrunk 3G™ unit, UT-117
- Programmable wide and narrow channel bandwidth (25/12.5kHz, 30/15kHz) and more...

OPTIONS

BATTERY PACKS

▲ BP-230 ▲ BP-231 ▲ BP-232

Battery packs	Type and capacity	Operating time* (VHF/UHF)	Output power (VHF/UHF)
BP-230	Li-Ion 7.4V/ 800mAh	6/6 hours	5W/4W
BP-231	Li-Ion 7.4V/1150mAh	9/8 hours	5W/4W
BP-232	Li-Ion 7.4V/2000mAh	16/15 hours	5W/4W

* Operating time is approximate time (at 20°C).
Tx: Rx: standby=5:5:90. Power save on.

RAPID CHARGER

▲ BC-145 ▲ BC-160 ▲ CP-17L ▲ OPC-515L

BC-160 DESKTOP CHARGER + BC-145 AC ADAPTER
Charges the BP-231 in 2 hours (approx.).

BC-119N DESKTOP CHARGER + AD-106 CHARGER ADAPTER + BC-145 AC ADAPTER : Charges the BP-231 in 2 hours (approx.).

CP-17L CIGARETTE LIGHTER CABLE, OPC-515L DC POWER CABLE
For use with the BC-160 or BC-119N. (12–16V DC required).

BELT CLIPS

▲ MB-93 ▲ MB-94

MB-93 : Swivel type. A fast and easy way to remove the transceiver from your belt.

MB-94 : Alligator type. Same as supplied.

MULTI-CHARGER

▲ BC-121N+AD-106 (6 pcs.) ▲ OPC-656 ▲ BC-124

BC-121N MULTI-CHARGER + AD-106 CHARGER ADAPTER + BC-124 AC ADAPTER

Rapidly charges up to 6 battery packs (Six AD-106s are required).
Charging time: approx. 2 hours when BP-231 is attached.

OPC-656 DC POWER CABLE : For use with the BC-121N. (12–20V DC required).

LEATHER BELT HANGERS

▲ MB-96N ▲ MB-96F

MB-96N: Swivel type belt hanger. Swivel joint of the MB-93 supplied.

MB-96F: Fixed type belt hanger. For use with MB-94.

HEADSETS and PTT/VOX UNIT

▲ HS-94 ▲ HS-95 ▲ HS-97 ▲ VS-1L

HS-94: Earhook headset with flexible boom microphone.

HS-95: Behind-the-head headset with flexible boom microphone.

HS-97: Throat microphone fits around your neck and picks up speech vibration.

VS-1L: PTT/VOX unit. Required when using these headsets with the transceiver.

SPEAKER-MICROPHONE

HM-131L : Durable body. Equipped with an earphone jack and revolving clip.

SP-13 : EARPHONE
Provides clear audio in noisy environments.

INTERNAL UNITS

UT-105 SmarTrunk II™ Board UT-108 DTMF DECODER UT-109 VOICE SCRAMBLER UNIT UT-113 MAN DOWN UNIT UT-117 SmarTrunk 3G™ Board

UT-105 : Provides SmarTrunk II™ capabilities.

UT-108 : Provides DTMF, Selective call and ANI capabilities.

UT-109 : Up to 32 scrambling codes are available. Version 02 is required.

UT-110 : Up to 1020 scrambling codes are available. Version 02 is required.

UT-113 : Automatically sends an emergency signal when the transceiver is left in a horizontal position for a preset time.

UT-117 : Provides SmarTrunk 3G™ and SmarTrunk II™ capabilities. Enhanced calling features available.

STUBBY ANTENNA

FA-SC73US

STUBBY ANTENNAS
• **FA-SC56VS** : 150–162MHz
• **FA-SC57VS** : 160–174MHz
• **FA-SC73US** : 450–490MHz

ANTENNAS
• **FA-SC25V** : 136–150MHz
• **FA-SC55V** : 150–174MHz
• **FA-SC25U** : 400–430MHz
• **FA-SC57U** : 430–470MHz
• **FA-SC72U** : 470–520MHz

SPECIFICATIONS

- | GENERAL | |
|--|--|
| • Frequency range | : |
| IC-F33GT/GS | 136–174MHz (U.S.A. and General) |
| IC-F43GT/GS | 400–470MHz (U.S.A. and General)
450–512MHz (U.S.A.)
450–520MHz (General) |
| • Number of channels | : 256 channels/16 banks |
| • Channel spacing | : 12.5kHz/25kHz, 15kHz/30kHz |
| • PLL channel step | : 2.5kHz, 3.125kHz (VHF)
5kHz, 6.25kHz (UHF) |
| • Antenna impedance | : 50Ω |
| • Usable temperature range | : -30°C to +60°C; -22°F to +140°F |
| • Power supply requirement | : 7.2V DC |
| • Current drain (at 7.2V DC; approx.): | |
| Transmit VHF/UHF | 1.5A/1.7A (at 5W/4W) |
| Receive stand-by | 85mA |
| rated output | 300mA |
| • Dimensions (with BP-231) | : 53 (W) ×120 (H) ×32.5 (D) mm;
(projections are not included) 2 ³ / ₃₂ (W) ×4 ²³ / ₃₂ (H) ×1 ⁹ / ₃₂ (D) in |
| • Weight (approx.) | : 285g; 10.0oz (VHF)
(with BP-231 and antenna) 300g; 10.6oz (UHF) |

- | TRANSMITTER | |
|---------------------------------|--|
| • Output power | : 5W (VHF), 4W (UHF) |
| • Max. frequency deviation | : ±5kHz (Wide)
±2.5kHz (Narrow) |
| • Frequency error | : ±2.5ppm |
| • Spurious emissions | : 80dB typ. (VHF)
70dB typ. (UHF) |
| • Adjacent channel power | : 70dB (Wide), 60dB (Narrow) |
| • FM Hum and Noise | : 46dB typ. (Wide)
40dB typ. (Narrow) |
| • Audio harmonic distortion | : 3% typ. (AF 1kHz, 40% deviation) |
| • Modulation limiting | : 60–100% of max. deviation |
| • External microphone connector | : 3-conductor 2.5 (d) mm (1/10")/2.2kΩ |

Measurements made in accordance with EIA/TIA-603. All stated specifications are subject to change without notice or obligation.

SmarTrunk II and SmarTrunk 3G are trademarks of SmarTrunk Systems, Inc. All other trademarks are the properties of their respective holders.

- | RECEIVER | |
|--------------------------------|--|
| • Intermediate frequency | : 1st 46.35MHz
2nd 450kHz |
| • Sensitivity | : 0.25µV typ. (at 12dB SINAD) |
| • Squelch sensitivity | : 0.25µV typ. (at threshold) |
| • Adjacent channel selectivity | : 75dB typ. (Wide)
65dB typ. (Narrow) |
| • Spurious response | : 70dB |
| • Intermodulation | : 74dB typ. |
| • Hum and noise ratio | : 45dB typ. (Wide)
40dB typ. (Narrow) |
| • Audio output power | : 500mW typ.
(at 5% distortion with an 8Ω load) |
| • External speaker connector | : 2-conductor 3.5 (d) mm (1/8")/8Ω |

Applicable U.S. Military Specifications

Icom makes rugged products that meet MIL-STD requirements and strict environmental standards as follows.

Standard	MIL 810C		MIL 810D		MIL 810E		MIL 810F	
	Method	Proc.	Method	Proc.	Method	Proc.	Method	Proc.
Low Pressure	500.1	I	500.2	I, II	500.3	I, II	500.4	I, II
High Temp.	501.1	I	501.2	I, II	501.3	I, II	501.4	I, II
Low Temp.	502.1	I	502.2	I, II	502.3	I, II	502.4-3	I, II
Temp. Shock	503.1	I	503.2	I	503.3	I	503.4	I
Solar Radiation	505.1	I	505.2	I	505.3	I	505.4	I
Rain	506.1	II	506.2	II	506.3	II	506.4	III
Humidity	507.1	I, II	507.2	II, III	507.3	II, III	507.4	-
Salt Fog	509.1	I	509.2	I	509.3	I	509.4	-
Dust	510.1	I	510.2	I	510.3	I	510.4	I
Vibration	514.2	VIII, X	514.3	I	514.4	I	514.4	I
Shock	516.2	I, II, V	516.3	I, IV	516.4	I, IV	516.5	I, IV

SUPPLIED ACCESSORIES (May differ according to version)



Icom Inc.

1-1-32, Kamiminami, Hirano-ku, Osaka 547-0003, Japan Phone: +81 (06) 6793 5302 Fax: +81 (06) 6793 0013 URL: <http://www.icom.co.jp/world/index.html>

Count on us!

Icom America Inc.
2380 116th Avenue N.E., Bellevue, WA 98004, U.S.A.
Phone: +1 (425) 454-8155
Fax: +1 (425) 454-1509
E-mail: sales@icomamerica.com
URL: <http://www.icomamerica.com>
<Customer Service> Phone: +1 (425) 454-7619

Icom New Zealand
146A Harris Road, East Tamaki, Auckland, New Zealand
Phone: +64 (09) 274 4062
Fax: +64 (09) 274 4708
E-mail: inquiries@icom.co.nz
URL: <http://www.icom.co.nz>

Icom (UK) Ltd.
Unit 9, Sea St., Herne Bay, Kent, CT6 8LD, U.K.
Phone: +44 (01227) 741741
Fax: +44 (01227) 741742
E-mail: info@icomuk.co.uk
URL: <http://www.icomuk.co.uk>

Asia Icom Inc.
6F No. 68, Sec. 1 Cheng-Teh Road, Taipei, Taiwan, R.O.C.
Phone: +886 (02) 2559 1899
Fax: +886 (02) 2559 1874
E-mail: sales@asia-icom.com
URL: <http://www.asia-icom.com>

Your local distributor/dealer:

Icom Canada
Glenwood Centre #150-6165 Highway 17, Delta, B.C., V4K 5B8, Canada
Phone: +1 (604) 952-4266
Fax: +1 (604) 952-0090
E-mail: info@icomcanada.com
URL: <http://www.icomcanada.com>

Icom (Europe) GmbH
Communication Equipment
Himmelgeister Str. 100,
D-40225 Düsseldorf, Germany
Phone: +49 (0211) 346047
Fax: +49 (0211) 333639
E-mail: info@icom-europe.com
URL: <http://www.icom-europe.com>

Icom France S.a
Zac de la Plaine, 1,
Rue Brindejone des Moulinais BP 5804,
31505 Toulouse Cedex, France
Phone: +33 (5) 61 36 03 03
Fax: +33 (5) 61 36 03 00
E-mail: icom@icom-france.com
URL: <http://www.icom-france.com>

Beijing Icom Ltd.
1305, Wanshang Plaza, Shijingshan Road, Beijing, China
Phone: +86 (010) 6866 6337
Fax: +86 (010) 6866 3553
E-mail: bjicom@bjicom.com
URL: <http://www.bjicom.com>

Icom (Australia) Pty. Ltd.
A.B.N. 88 006 092 575
290-294 Albert Street, Brunswick, Victoria, 3056, Australia
Phone: +61 (03) 9387 0666
Fax: +61 (03) 9387 0022
E-mail: sales@icom.net.au
URL: <http://www.icom.net.au>

Icom Spain S.L.
Ctra. de Gracia a Manresa Km. 14,750
08190 Sant Cugat del Valles Barcelona, Spain
Phone: +34 (93) 590 26 70
Fax: +34 (93) 589 04 46
E-mail: icom@icomspain.com
URL: <http://www.icomspain.com>

Icom Polska
Sopot, 3 maja 54, Poland
Phone: +48 (58) 550 7135
Fax: +48 (58) 551 0484
E-mail: icompolksa@icompolksa.com.pl
URL: <http://www.icompolksa.com.pl>



Icom Inc. (Japan), is an ISO 9001 and ISO 14001 certification acquired company.