



**SCHEMATIC OF THE
HEATHKIT®
MODEL HW-8
TRANSCEIVER**

Copyright © 1975
Heath Company
All Rights Reserved

Part of 595-1754-10

NOTES:

1. CIRCUIT COMPONENT NUMBERS ARE IN THE FOLLOWING GROUPS:
 - 1 - 199 PARTS MOUNTED ON MAIN CIRCUIT BOARD.
 - 201 - 225 PARTS MOUNTED ON A.F. AMPLIFIER CIRCUIT BOARD.
 - 301 - 325 PARTS MOUNTED ON CHASSIS.
2. ALL RESISTOR VALUES ARE IN OHMS (K-1,000; M-1,000,000).
3. ALL CAPACITOR VALUES LESS THAN 1 ARE IN μ F. VALUES OF 1 AND ABOVE ARE IN pF UNLESS OTHERWISE INDICATED.
4. (TP) THIS SYMBOL INDICATES A TEST POINT.
5. THIS SYMBOL INDICATES A RECEIVE-MODE DC VOLTAGE MEASURED FROM THE POINT INDICATED TO CHASSIS.
6. THIS SYMBOL INDICATES A TRANSMIT-MODE DC VOLTAGE MEASURED FROM THE POINT INDICATED TO CHASSIS.
7. THIS SYMBOL INDICATES A RECEIVE-MODE RF VOLTAGE MEASURED USING AN RF PROBE CONNECTED BETWEEN THE POINT INDICATED AND CHASSIS.
8. THIS SYMBOL INDICATES A TRANSMIT-MODE RF VOLTAGE MEASURED USING AN RF PROBE CONNECTED BETWEEN THE POINT INDICATED AND CHASSIS.
9. ALL VOLTAGES MEASURED WITH A HIGH INPUT IMPEDANCE VOLTMETER. VOLTAGES MAY VARY \pm 2%.
10. ALL MEASUREMENTS OBTAINED USING A POWER SOURCE OF 13 VDC.
11. BANDSWITCH SHOWN WITH 3.5 MHz PUSHBUTTON PRESSED IN AND TRANSCEIVER OPERATING IN RECEIVE MODE.

